

# UPM Raflatac Technical Information

08.08.2012 ENG 552

SELF-ADHESIVE	SHEETS
FACE	POLYLASER MATT WHITE HS
A4 Filmics	AXL (sales code)
Product	White, heat stabilized, matt coated computer imprintable polyester film.
Use	Information labelling where overprinting is made by laser or thermal transfer. Recommended for drum and logistics labelling. Specially developed for medium and high volume laser printers.

## Typical technical values

Substance	75	g/m <sup>2</sup>	DIN 53352
Caliper	58	µm	DIN 53370
Elongation MD	150.0	%	DIN 53455
Elongation CD	130.0	%	DIN 53455
Opacity	88	%	DIN 53146/1

Printability Due to the pre-treatment, the film is printable by common label printing methods like letterpress, flexography, screen and offset. Special inks designed for nonabsorbent materials should be used. Laser and copier printable: specially developed for medium and high volumes.

Shelf life Laminate with RP37, RP77, SP37 and RR28 adhesives 2 years if stored at room temperature (+20°C, 50% RH) in original packaging and protected from light.

Warranty Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use.

This publication replaces all previous versions. All information is subject to change without notice.



**UPM**

[www.upmraflatac.com](http://www.upmraflatac.com)